



(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
**14.03.2001 Bulletin 2001/11**

(51) Int Cl.7: **G06F 17/22, G06F 17/21**

(43) Date of publication A2:  
**14.04.1999 Bulletin 1999/15**

(21) Application number: **98308064.9**

(22) Date of filing: **05.10.1998**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: **06.10.1997 JP 27249097**  
**22.09.1998 JP 26876298**

(71) Applicant: **MATSUSHITA ELECTRIC INDUSTRIAL**  
**CO., LTD**  
**Kadoma-shi, Osaka 571-0000 (JP)**

(72) Inventors:  
• **Hishida, Toshihiro**  
**Kobe-shi, Hyogo-ken 651-1123 (JP)**  
• **Ohto, Hidetaka**  
**Takarazuka-shi, Hyogo-ken 665-0847 (JP)**

(74) Representative: **Crawford, Andrew Birkby et al**  
**A.A. Thornton & Co.**  
**235 High Holborn**  
**London WC1V 7LE (GB)**

(54) **A transmission document edition device, a received document processing device, a server device in a communication document processing system, and a computer-readable record medium that stores the function**

(57) A transmission document edition device edits a transmission document to be transmitted to a variety of mobile communication terminals from a document described in a markup language. A document content temporarily storage unit stores a document including a plurality of document elements to be transmitted. A device input/output information storage unit stores a plurality of pieces of device input/output information that indicate the document elements to be transmitted for a plurality

of types of mobile communication terminal. A transmission document creation unit creates a transmission document including the document and the plurality of pieces of device input/output information. A simulation operation execution unit obtains the piece of device input/output information corresponding to the designated type of mobile communication terminal from the transmission document, selects the document element indicated in the obtained device input/output information, and creates display data.